

SelectSeal

Material Safety Data Sheet

CT100 PAVEMENT SEALER

Date: 1/1/2012

Chemical Formula: Mixture

SECTION 1 – MANUFACTURER INFORMATION

Manufacturer's Name: Select Seal
Address: 2122 Gould Ct, Rockdale IL 60436
Emergency Phone No.: CHEMTREC 1-800-424-9300 24 HOURS
Information Phone No.: 847-417-1066

SECTION II – HAZARDOUS INGREDIENTS

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>	<u>% BY WEIGHT</u>	<u>TLV</u>
Hydrous Aluminum Silicate	1332-58-7	25 ±5	N/A
Refined Coal Tar Pitch	65996-93-2	25 ±5	.07mg/m ³
Water	7732-18-5	49 ±5	NDA
Additives	Proprietary	1 ± 0.5	N/A

SECTION III – PHYSICAL DATA

APPEARANCE: BLACK, VISCOUS LIQUID
ODOR: LIGHT, "CREOSOTE" ODOR

BOILING POINT: SAME AS WATER (H₂O) EVAPORATION RATE (BUTYL ACETATE=1): SAME AS WATER (H₂O)
VAPOR PRESSURE (mmHG): 17 SPECIFIC GRAVITY (WATER=1): 1.32
WATER SOLUBILITY: DISSOLVES IN WATER MELTING POINT: N/A
VAPOR DENSITY (Air=1): SAME AS WATER (H₂O)

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS: N/A
FLASH POINT: NONE
EXTINGUISHING METHOD: DRY CHEMICAL, CO₂, FOAM, H₂O, FOG
UNUSUAL FIRE OR EXPLOSION HAZARDS: CO, CO₂, OXIDES OF NITROGEN, COAL TAR PITCH VOLATILES

SPECIAL FIRE-FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS RECOMMENDED FOR PROTECTION AGAINST EXPOSURE TO COAL TAR VOLATILES (DRIED MATERIAL). WILL NOT BURN IN LIQUID STATE.

SECTION V – PHYSICAL HAZARDS (REACTIVITY DATA)

STABILITY (THERMAL, LIGHT): STABLE
INCOMPATIBILITY (MATERIAL TO AVOID): AVOID CONTACT WITH STRONG OXIDIZERS
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂, OXIDES OF NITROGEN, COAL TAR PITCH VOLATILES

SECTION VI – HEALTH HAZARDS

ROUTE(S) OF ENTRY: INHALATION? YES SKIN? YES INGESTION? YES EYES? YES
HEALTH HAZARDS (ACUTE & CHRONIC): PROLONGED EXPOSURE CAN CAUSE SKIN IRRITATION. PROLONGED AND REPEATED EXPOSURE TO CTPV (Coal Tar Pitch Volatiles) IS ASSOCIATED WITH INCREASED RISK OF CANCER OF THE LUNGS, SKIN, BLADDER, AND KIDNEYS.
CARCINOGENICITY: NTP? YES IARC MONOGRAPHS? NO OSHA REGULATED? NO
SIGNS AND SYMPTOMS OF EXPOSURE: PROLONGED SKIN CONTACT MAY CAUSE DERMATITIS.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN

SECTION VII – EMERGENCY & FIRST AID

SKIN: WASH WITH SOAP AND CLEAN WATER
EYES: FLUSH WITH CLEAN WATER

CT100 PAVEMENT SEALER – Page 2

SECTION VIII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: RECOVER SPILLED MATERIAL WITH SCOOP OR SHOVEL. MAY BE REUSED.

WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE ABOVE FREEZING

OTHER PRECAUTIONS: AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

SECTION IX – CONTROL MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): NONE REQUIRED

VENTILATION:

LOCAL EXHAUST: NONE

SPECIAL: NONE

MECHANICAL (GENERAL): NONE

OTHER: NONE

PROTECTIVE GLOVES: YES

EYE PROTECTION: YES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: IMPERVIOUS CLOTHING TO PREVENT SKIN CONTACT. BARRIER CREAM OR SUN BLOCK #15.

WORK/HYGENIC PRACTICES: USE GOOD HOUSEKEEPING PRACTICES

SECTION X – OTHER INFORMATION

	Health	Flammability	Reactivity
HMIS** Rating	1*	0	0
NFPA*** Rating			

Notice: These ratings involve data and interpretations that may vary from company to company and are intended only for rapid general identification of the magnitude of the specific hazard. TO DEAL ADEQUATELY WITH THE SAFE HANDLING OF THIS MATERIAL ALL OF THE INFORMATION CONTAINED IN THIS MSDS MUST BE CONSIDERED. The customer is responsible for determining the proper personal protective equipment needed for its particular use of this material.

** Hazardous Materials Identification Systems [HMIS] Revised RAW MATERIALS RATING MANUAL, National Paint & Coatings Association, Fall 1984

*** NFPA 704 Standard System for the Identification of the Fire Hazards of Materials, National Fire Protection Association, 1985

The information contained herein is furnished without warranty of any kind. Users should consider this data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers. Information on this form is furnished solely for the purpose of compliance with OSHA Hazard Communication Standard, 20 CFR 1910.1200, the Workplace Hazardous Material Information System (WHMIS), and shall not be used for any other purpose.